HARLEQUIN CAP RANGE



DURABLE & COMPACT

TANK LIFE EXPECTANCY

Sewage Treatment Systems



www.harlequinplastics.co.uk

NORTHERN IRELAND | ENGLAND









Harleguin®
MANUFACTURING FOR TOMORROW



CAP RANGE

Harlequin CAP (Continuous Aeration Process) Sewage Treatment Plants are perfect for the treatment of sewage waste and suitable for discharge to both watercourse or drainage field*. The compact design and robust MDPE tank body is complemented by a small tank lid and movable tank compressor box making it an ideal product to tuck away in your garden.







CAP 9



MARKET LEADING

POLLUTANT REMOVAL

96.2%







CAP 18

KEY FEATURES



Super Quiet**



Pollutant Removal Level of 96.2%



Reliable Bio Media System



Durable and Stable Product Design



Odourless



Low Maintenance Costs



Compact System



2-year Warranty***



Small Low Profile Covers



Certified for use in the UK in compliance with EN12566-3



Adjustable risers available for ideal invert fit

| Model | CAP6 | CAP9 | CAP12 | CAP15 | CAP18 |
|-------------------------------------|------|------|---------|---------|---------|
| Population Served | | | 10-12 | 13-15 | 16-18 |
| Desludging Intervals (Months) | 12* | 12* | 12* | 12* | 12* |
| Inlet Invert (mm) | 650 | 550 | 500 | 600 | 600 |
| Outlet Invert (mm) | 825 | 625 | 660 | 750 | 750 |
| Blower Ratings | 40W | 76W | 105W | 105W | 112W |
| Length (mm) | 1660 | 1840 | 2900 | 3615 | 3615 |
| Width (mm) | 1600 | 1840 | 1620 | 1620 | 1620 |
| Height (mm) | 2180 | 2180 | 2000 | 2140 | 2140 |
| Weight (Kg) | 275 | 350 | 460 | 600 | 600 |
| Cover Sizes (mm) | 450 | 450 | 600x450 | 600x450 | 600X450 |

Manhole riser kits available | Pumped outlets available *Desludge interval depending on usage

**When installed in accordance with manufacturers instructions

EXTERNAL BLOWER

All sewage treatment plants come with an external blower for optimal performance. The blower is located in a weatherproof aboveground external housing.





Internal view of CAP 6, 9 & 12

^{*}Subject to local regulations

^{***2} year warranty only when product is registered on our website